

# HTJ-1100 BIGGER AND BETTER

One Inch Printhead Thermal Inkjet Printer



## HTJ-1100 THERMAL INKJET PRINTER



#### **TECHNICAL SPECIFICATIONS**

Dimensions (L x W x H)

Weight

Technology

Hi-Speed USB 2.0

**Control method** 

**External connection** 

**Build in sensor** 

Mounting brackets

Anti-Shock

**Material housing** 

**Operating language** 

107.5 x 74.5 x 83mm

526.6g

Thermal Inkjet

2 USB ports

Wireless keyboard

External Sensor, External Encoder, Alarm Beacon

Available

Available

Available

Black anodized aluminum

English (Default), Finnish, Spanish, Deutsch, French, Russian, Vietnamese, Chinese,

Korean, Portuguese, Polish, Dutch, Italian, Turkish, Czech and Indonesian

#### **FEATURES**

**Printability** 

**Maximum characters** 

Maximum messages length

Messages height

Messages storage

Print speed

Resolution

**Density** 

Printing distance

Print mode

Print direction

**Printable surface** 

External device

Text, Logo, Barcode 1D, Counter, Shift code, Box/Lot, Date, Time and Expiry date

150 characters / messages (Latin message)

75 characters / messages (Chinese message)

~ 3 meters

2.54 - 25.4 mm

100 messages

Maximum up to 76 m/min at 300x300 dpi

Maximum 300x300 dpi

Support: 300x300, 300x150 and 300x100 dpi

3 levels

1-6 mm

Continuous mode, Sensor mode and Repeat mode

Left to right, Right to left, Left to right reverse and Right to left reverse

Flat, Curve (pipe), Porous, Semi-Porous, Non-Porous

PLC via RS485 protocol

#### **INK AND SUBSTRATE CAPABILITIES**

Ink type Colors

Bulk Ink delivery system Ink security technology

Solvent-based and Water-based inks

• • •

Available

Smart chip

#### **OPERATING ENVIRONMENT**

Power supply Operating Temperatures

12VDC - 5A , 60W 5 - 50°C

### Distributed by: Hitachi Asia Ltd.

(Industrial Components & Equipment Group)

30 Pioneer Crescent #10-15 West Park Bizcentral, Singapore 628560

Tel: (65) 6305 7400 Fax: (65) 6305 7401