



## ON-LINE THERMAL INKJET PRINTER MODEL P100

**Upto 12.7 mm Single Head Print**



Nozzle	TIJ 2.5 Thermal Foaming
CPU	Quad Core 1.4Hz
Language	English (Total 20 languages)
Touch Screen	4.3" (Inches)
Print Height	12.7mm
Print Distance	1mm to 5mm
Print Content	Text, Date, Batch No, Symbol & Serial No, Table, Linear Barcode & QR Code
Definition	300 & 600 dpi – Jet Time: Light to Bold
Storage	100 Messages
Printing Length	2000 Characters of 5mm for each message
Printing Speed	30 to 50 mtr/min
Ink Color	Black (Regular)
Ink Cartridge Solvent Based	42ml (Approx. 25 to 28 lakh characters of 3mm can be printed with 300 dpi)
Cartridge Storage	AC Room (better) or Normal Room Temperature. Cartridge should be capped always when not in use.
External Interface	USB, Photoelectric Interface, can directly insert a USB to upload information
Adapter Input Voltage	230V AC
Printer Input Voltage	16V – 1.5A
Power Consumption	Lower than 5w
Working Environment	Temperature 0 ~ 35 Degrees / Humidity: 10%~80%
Printing Material	Carton, Stone, Pipe, Cable, Metal, Plastic Product, Electronic, Fibre Board

